


## Микроаксиальный кабель 1.32mm

<b>Product Type</b>		<b>1.32mm</b>		
<b>Structure Drawing</b>				
<b>Structure Characteristics</b>				
<b>Structure</b>	<b>Item</b>	<b>Standard Value</b>		
Conductor	Material	Silver Cover Copper		
	Construction(mm)	7/0.085		
	Nom.Dia(mm)	0.22		
Insulation	Material	FEP		
	Nom.Dia(mm)	0.05		
Shield	Material	Silver Cover Copper		
	Nom.Dia(mm)	0.81		
Jacket	Material	FEP		
	Nom.Dia(mm)	1.32		
<b>Electrical Characteristics</b>				
<b>Item</b>	<b>Standard Value</b>	<b>Attenuation and Power handling@25°C and Sea Level</b>		
		<b>Frequency (MHz)</b>	<b>Attenuation (dB/m)</b>	<b>Power handling ( w )</b>
Impedance (Ω)	50	1000	1.6	
Capacitance(pF/m)	96	2000	2.2	
Max Operating Frequency(GHz)	8	2400	2.5	
Max Conductor Resistance(Ω/km)	850	6000	4.2	
Insulation Resistance (at20°C) (MΩ.km)	1000	8000	5.1	
<b>Mechanical &amp; Environmental Characteristics</b>				
Min Bending Radius/Single		mm	5.5	
Maximum tensile strength		kg	1.76	
Weight		kg/km		
Operating Temperature		°C	-55-+180	

1.32mm