


## Коаксиальные кабели серии RG

Product Type		RG213		
Structure Drawing				
Structure Characteristic				
Structure	Item	Standard Value		
Inner Conductor	Material	Bare copper		
	Construction(mm)	7/0.75		
	Nom.Dia(mm)	2.25		
Insulation	Material	PE		
	Nom.Dia(mm)	7.25		
Wire braid	Material	Bare copper		
	Nom.Dia(mm)	8.05		
Jacket	Material	PVC		
	Nom.Dia(mm)	10.30		
Electrical Characteristics				
Item	Standard Value	Attenuation and Power handling@25°C and Sea Level		
		Frequency (MHz)	Attenuation (dB/100m)	Power handling ( w )
Impedance (Ω)	50±2	0.1GHz	7.20	
Capacitance(pF/m)	105±5	0.2GHz	10.50	
Velocity( %)	66	0.4GHz	14.10	
VSWR	≤1.25@DC-2.5MHz	0.8GHz	23.50	
Max Operating Voltage(v)	3700	1.0GHz	27.50	
Max Operating Frequency(GHz)	1.0			
Mechanical & Environmental Characteristics				
Min Bending Radius/Single		mm	50	
Weight		kg/M		
Operating Temperature		°C	-20-+80	